



- NOTE:
1. Material: Insulator: PC+ABS, rated UL94V-0, color: black. Contacts: Phosphor Bronze, Selected Gold on Contact Area Plating.
 2. Durability : 10000 cycles MIN.cycle
 3. No burr and no square edge.
 4. Contact Resistance: 100mΩ Max.
 5. Dielectric Withstanding Voltage: 500VAC Max With 1 Minute
 6. Insulation Resistance:1000 MΩ Min.
 7. Current Rating: 1 A AC/DC Max. Rated Voltage: 500 V RMS Min.
 8. Mini SD Card extraction force: 1.5N MIN.
 9. Durability: 10,000 mating cycles.
 10. Operating Temperature: -25℃ ~ +85℃
 11. Storage Temperature:-45

TABLE 1:

1-183-400232-007	8u" GOLD
1-183-400232-006	30u" GOLD
1-183-400232-005	15u" GOLD
1-183-400232-004	10u" GOLD
1-183-400232-003	5u" GOLD
1-183-400232-002	3u" GOLD
1-183-400232-001	1u" GOLD

TOLERANCES UNLESS OTHERWISE SPECIFIED:
 0 P/LC ± 0.30
 1 P/LC ± 0.20
 2 P/LC ± 0.15
 ANGLES ± 3°

FINISH SEE NOTE
 MATERIAL SEE NOTE
 DWG CHK DATE
 DORIS TSOI 16-MAR-2007
 KEVIN KE 16-MAR-2007
 JACKY LIN 16-MAR-2007
 WEIGHT --- GRAM
 PRODUCT SPEC SEE NOTE
 LOC SIZE DRAWING NO C-400232
 DW A4
 SCALE 1:1
 SHEET 1 OF 1
 REV A

Pin No.

P1	CD\DAT3	P4	VDD	P7	DATO	P10	NC ⁴
P2	CMD	P5	CLK	P8	DATI	P11	NC ⁴
P3	VSS1	P6	VSS2	P9	DAT2		

LTR	REVISION RECORD	ECN	DATE
A	FIRST RELEASED	GMT200703-183	03/16